Technical specification Of Motor cycle

Quantity-Eight		े विति भी	
S.N.	Criteria	Requirement	Offered Specification
1		Model Suitable for Rough road condition, Kerb	Make:
	general	Weight of Motorcycle Minimum 130 KG, Wheel base	Model:
		Minimum 1300 mm .	
2	Engine	4stroke Aircooled petrol engine, engine displacement	
		150cc,(+_2%),developing power output not less	п
		than 13ps at governed RPM with torque min.12N-m.	
3	Transmission	5 speed constant mesh .	
4	Tyre	Standard size, Factory fitted tubeless .	
5	Brakes	Hydraulic operated disc/drum type .	
6	Fuel tank	Minimum 12 liters . All signs and instruction shall be in english .	
	Capacity		
	Instruction	one copy of opertors/owners instruction and	
8	Manual	maintenance manual in english shall be suplied with	
		motorcycle.	
		a set of tools required for general maintenance shall	
	Tools	1	
10	College	Supplied . Standard colour	
10	Colour Warranty	Manufacturer shall provide one year warranty after	
12	Ground	acceptance .	
	clearance	Minimum 160mm.	
13	1	12V DC .	
13	Suspension	telescopic, nitrox shockabsorber, monoshock, Swingram	
14		at front&rear.	
	Cranina	at nontexteat.	
15	Starting method	Electric &kick .	
16	Emission	The Emission standard of the vechicle should be of	. 2
	standard	Capable of meeting apllicable "Nepal vechicle Mass	
		Emission standard2069", Which is to be certified by	2.5
		department of transport management .	
17		1.The Motorcycle offered shall be a current model	
	Comment of the Commen	under standard production by the manufacturer for at	
	Proven	least one year .	
	performance	2.The bidder shall provide the manufacturer's data of	
		the performance of the unit to include the fuel	
		consumption, performance curve of the engine etc.	
		The Motorcycle Four Unit shall be delivery to:-	
18	Delivery	Kerabari Rural municipality.	g ^l

Note: The major items are indicated by bold and highlighted letters/alphabets/figures in the technical specification

Bidder's signature.....

Date.....

प्रमुख प्रशासकीय अधिकत